

Product Specifications

HEXXTILE PROGRESSION



2511
Steel Shot
HX

2513
Nickel
HX

2520
Cliff Face
HX

2524
Night Sky
HX

2531
Graphite
HX

2534
Black Ice
HX

2542
Volcanic
HX

Dimensions



Tile Size
433 x 500mm



Total Weight
4,300g/m²



Pile Weight
Plain/Stripe - 500g/m²
Design - 515g/m²



Total Thickness
5mm

Construction

Pile Type
100% Suprona™ nylon

Tuft Density
145,600/m²

Technical Data



Fire Rating
ISO 13501-1 Bfl-S1



Dimensional Stability
BS EN 986:2005 <0.2%



Light Fastness
ISO 105 >6

Shampoo Fastness
ISO 105 min 4-5



Antistatic
EN 6356 < 2kV
Permanently Antistatic

Colour Fastness (Water)
ISO 105 min 4-5



Castor Chair Test
EN 985 - A: Suitable for
continuous use

Thermal Resistance
BS 4745:2005 0.44 Togs



Wear Rating
BS EN 1307 Class 33 Heavy Contract

HEXXTILE BRIGHT IDEAS



2516
Electricity
HX

2521
Roomba
HX

2529
Jet Engine
HX

2539
Fibre Optic
HX

2546
Broadband
HX

Dimensions



Tile Size
433 x 500mm



Total Weight
4,100g/m²



Pile Weight
580g/m²



Total Thickness
6.2mm

Construction

Pile Type
100% Polyamide

Tuft Density
161,950/m²

Technical Data



Fire Rating
ISO 13501-1 Bfl-S1



Dimensional Stability
EN 986 ≤ 0.20%



Wear Rating
BS EN 1307
Class 33
Heavy Contract



**Impact Sound
Reduction**
ISO 140-80 24dB



Sound Absorption
EN ISO 11654 α_w 0.15

f/Hz	125	250	500	1000	2000	4000
α_s	0.00	0.03	0.06	0.14	0.30	0.34

01592 630 030
uksales@duraflor.com

DURAFLOR.COM

All colours are for illustrative purposes only.
If colour choice is critical, please request a sample